



US009410920B2

(12) **United States Patent**
Ferry

(10) **Patent No.:** **US 9,410,920 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **APPARATUS AND ITS ARRANGEMENT
WITH DUCT TO DETERMINE FLOWABLE
MEDIUM PARAMETERS**

(71) Applicant: **ALSTOM Technology Ltd**, Baden (CH)

(72) Inventor: **Allan Gunn Ferry**, Windsor, CT (US)

(73) Assignee: **ALSTOM TECHNOLOGY LTD**,
Baden (CH)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 377 days.

(21) Appl. No.: **13/914,791**

(22) Filed: **Jun. 11, 2013**

(65) **Prior Publication Data**

US 2014/0360249 A1 Dec. 11, 2014

(51) **Int. Cl.**

G01N 33/00 (2006.01)

G01N 27/407 (2006.01)

G01K 13/02 (2006.01)

(52) **U.S. Cl.**

CPC **G01N 27/4073** (2013.01); **G01K 13/02**
(2013.01); **G01N 33/0004** (2013.01)

(58) **Field of Classification Search**

CPC G01N 22/0004; G01N 22/0009
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,246,799 A 11/1917 Wilson
2,140,562 A * 12/1938 Snow G01F 25/0053
73/1.16

3,600,933 A * 8/1971 Johnston G01N 25/04
374/23
4,155,245 A * 5/1979 Coe G01N 25/68
374/21
5,106,203 A 4/1992 Napoli et al.
5,217,692 A * 6/1993 Rump G01N 33/0031
73/31.05
2004/0042527 A1 3/2004 Block et al.
2006/0289308 A1 * 12/2006 Shaddock F01N 13/08
204/424
2007/0137318 A1 6/2007 Desrochers et al.

FOREIGN PATENT DOCUMENTS

DE 38 43 233 A1 6/1990
DE 44 38 523 C1 12/1995

* cited by examiner

Primary Examiner — Michael A Lyons

Assistant Examiner — Alex Devito

(74) *Attorney, Agent, or Firm* — GE Global Patent
Operation; Stephen G. Midgley

(57)

ABSTRACT

An apparatus is mountable to a duct having a cross-section, for determining parameters of a flowable medium flowing through the duct. The apparatus includes a mounting attachment having a conduit member, and at least one combination of multiple sensing members configured to the conduit member. The conduit member may be disposed entirely within the duct such that the multiple sensing members are located within the duct establishing direct contact with the flowable medium. The multiple sensing members include oxygen and temperature sensing elements respectively, to determine parameter such as oxygen level in the flowable medium, and temperature of the flowable medium. Several such apparatus may be mounted in the duct across the cross-section to define a grid to determine said parameter at various locations across the cross-section.

20 Claims, 6 Drawing Sheets

